



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	LPS® PreSolve (Aerosol)
Registration number	-
Synonyms	None.
Part Number	01420, M01420
Issue date	15-September-2015
Version number	03
Revision date	23-March-2016
Supersedes date	04-November-2015

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	A solvent degreasing agent designed for removing tar, adhesives, grease, oil and other residues from metal and other hard surfaces.
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier	Alsco Ltd
Company name	Unit 13 Hillmead Industrial Estate
Address	Marshall Road Swindon, Wiltshire United Kingdom SN5 5FZ
Telephone	+44 1793 733 900
In Case of Emergency	+001 703-527-3887
Manufacturer	
Company name	ITW Pro Brands
Address	4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)
Website	http://www.lpslabs.com
e-mail	lpssds@itwprobrands.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F+;R12, Xi;R36/38, R43, N;R51/53

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

Environmental hazards

Hazardous to the aquatic environment,
long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with
long lasting effects.

Hazard summary**Physical hazards**

Extremely flammable.

Health hazards

Irritating to eyes and skin. May cause sensitisation by skin contact. Occupational exposure to the substance or mixture may cause adverse health effects.

Environmental hazards

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Specific hazards

Extremely flammable. Irritating to eyes and skin. May cause sensitisation by skin contact. Do not breathe dust/fume/gas/mist/vapors/spray. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Main symptoms

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. May cause redness and pain. Dermatitis. Rash.

2.2. Label elements**Label according to Regulation (EC) No. 1272/2008 as amended****Contains:**

Distillates Petroleum Hydrotreated Light, d-limonene

Hazard pictograms**Signal word**

Danger

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing gas.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear eye protection/face protection.
P280	Wear protective gloves.

Response

P302 + P352	IF ON SKIN: Wash with plenty of water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see this label).
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

Storage

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information

17,4 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Distillates Petroleum Hydrotreated Light	60 - 70	64742-47-8 265-149-8	-	649-422-00-2	
Classification:		DSD: Xn;R65			
		CLP: Flam. Liq. 3;H226, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336			
3-Methoxy-3-methyl-1-butanol (MMB)	10 - 20	56539-66-3 260-252-4	-	-	
Classification:		DSD: Xi;R36			
		CLP: Eye Irrit. 2;H319			
d-limonene	10 - 20	5989-27-5 227-813-5	-	601-029-00-7	
Classification:		DSD: R10, Xn;R65, Xi;R38, R43, N;R50/53			C
		CLP: Flam. Liq. 3;H226, Asp. Tox. 1;H304, Skin Irrit. 2;H315, Skin Sens. 1;H317, Aquatic Acute 1;H400, Aquatic Chronic 1;H410			C
Carbon dioxide	1 - 3	124-38-9 204-696-9	-	-	#
Classification:		DSD: -			
		CLP: -			

List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information

In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control centre immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Rash. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is stopped.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Extremely flammable aerosol.
5.1. Extinguishing media	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch or walk through spilled material. Avoid inhalation of vapours or mists. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapours or divert vapour cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
6.4. Reference to other sections	Use personal protection recommended in Section 8 of the SDS. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapour. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.
7.2. Conditions for safe storage, including any incompatibilities	Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits**Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	18000 mg/m ³
		10000 ppm
	MAK	9000 mg/m ³ 5000 ppm

Belgium. Exposure Limit Values.

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	54784 mg/m ³
		30000 ppm
	TWA	9131 mg/m ³ 5000 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	MAC	9000 mg/m ³
		5000 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
3-Methoxy-3-methyl-1-butan ol (MMB) (CAS 56539-66-3)	Ceiling	200 mg/m ³
	TWA	100 mg/m ³
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m ³
	TWA	9000 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m ³
		5000 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m ³
		5000 ppm
d-limonene (CAS 5989-27-5)	STEL	280 mg/m ³
		50 ppm
	TWA	140 mg/m ³ 25 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m ³
		5000 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3	
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5000 ppm 140 mg/m3	Vapor and aerosol.
d-limonene (CAS 5989-27-5)	TWA	20 ppm 28 mg/m3	Vapor and aerosol.
		5 ppm	

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	AGW	9100 mg/m3
d-limonene (CAS 5989-27-5)	AGW	5000 ppm 28 mg/m3
		5 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
	TWA	5000 ppm 9000 mg/m3 5000 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m3
	TWA	15000 ppm 9000 mg/m3 5000 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Netherlands. OELs (binding)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3
		5000 ppm
d-limonene (CAS 5989-27-5)	TLV	140 mg/m3
		25 ppm

Poland. MACs. Regulation regarding maximum permissible concentrations and intensities of harmful factors in the work environment, Annex 1

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m3
	TWA	9000 mg/m3

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9150 mg/m3
		5000 ppm

Sweden. Occupational Exposure Limit Values

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	18000 mg/m ³
	TWA	10000 ppm
		9000 mg/m ³
		5000 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
d-limonene (CAS 5989-27-5)	STEL	80 mg/m ³
	TWA	14 ppm
		40 mg/m ³
		7 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m ³
	TWA	15000 ppm
		9150 mg/m ³
		5000 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the GEN standards and in discussion with the supplier of the personal protective equipment. Use personal protective equipment as required.

Eye/face protection Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Skin protection

- Hand protection Chemical resistant gloves are recommended.

- Other Avoid contact with clothing. Wear suitable protective clothing. Chemical resistant gloves.

Respiratory protection No personal respiratory protective equipment normally required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards Not applicable.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Contain spills and prevent releases and observe national regulations on emissions. Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Gas.
Form	Aerosol
Colour	Clear, Off-white.
Odour	Orange
Odour threshold	Not established
pH	Not applicable
Melting point/freezing point	Not established
Initial boiling point and boiling range	> 150 °C (> 302 °F)
Flash point	40,0 °C (104,0 °F) Tag closed cup
Evaporation rate	> 0,1 BuAc
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0,7 %
Flammability limit - upper (%)	6 %
Vapour pressure	< 5 mm Hg @ 20°C
Vapour density	> 1 (Air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 15 %
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not established
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not established
Viscosity	< 3 cSt @ 25°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information

Heat of combustion	> 30 kJ/g
Percent volatile	100 %
Specific gravity	0,82 - 0,86 @ 20°C
VOC (Weight %)	97,2 % per U.S State and Federal Consumer Product Regulations.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions. Risk of ignition.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness.
Skin contact	Causes skin irritation. May cause sensitisation by skin contact.
Eye contact	Causes eye irritation.

Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Vapours have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.1. Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test results
3-Methoxy-3-methyl-1-butanol (MMB) (CAS 56539-66-3)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Mouse	5830 mg/kg
	Rat	> 2000 mg/kg
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
Inhalation		
<i>Aerosol</i>		
LC50	Cat	> 6,4 mg/l, 6 Hours
	Rat	> 7,5 mg/l, 6 Hours > 4,3 mg/l, 4 Hours
<i>Vapour</i>		
LC50	Rat	> 0,1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg
d-limonene (CAS 5989-27-5)		
Acute		
Oral		
LD50	Mouse	5600 - 6600 mg/kg
	Rat	> 2000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory sensitisation	Not a respiratory sensitizer.	
Skin sensitisation	May cause sensitisation by skin contact.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
d-limonene (CAS 5989-27-5)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Narcotic effects.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not likely, due to the form of the product.	
Mixture versus substance information	Not available.	
Other information	Not available.	

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test results
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2,9 mg/l, 96 hours
d-limonene (CAS 5989-27-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia pulex) 69,6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 0,619 - 0,796 mg/l, 96 hours
12.2. Persistence and degradability	Not inherently biodegradable.	
12.3. Bioaccumulative potential	No data available.	
Partition coefficient n-octanol/water (log Kow)		
d-limonene	4,232	
Bioconcentration factor (BCF)	Not available.	
12.4. Mobility in soil	Readily absorbed into soil.	
12.5. Results of PBT and vPvB assessment	Not available.	
12.6. Other adverse effects	None known.	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	Not available.
Tunnel restriction code	D
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

RID

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1

Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

ADN

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

Other information

Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable, MARINE POLLUTANT
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.
14.5. Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
14.6. Special precautions for user	Not available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

ADN; ADR; IATA; IMDG; RID





SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances

d-limonene (CAS 5989-27-5)

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

d-limonene (CAS 5989-27-5)

Directive 94/33/EC on the protection of young people at work, as amended

d-limonene (CAS 5989-27-5)

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work. Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.
R12 Extremely flammable.
R36 Irritating to eyes.
R36/38 Irritating to eyes and skin.
R38 Irritating to skin.
R43 May cause sensitisation by skin contact.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Revision information

Product and Company Identification: Product and Company Identification
SECTION 2: Hazards identification: GHS Signal Words
SECTION 3: Composition/information on ingredients: Component information
SECTION 5: Firefighting measures: Unsuitable extinguishing media
SECTION 5: Firefighting measures: General fire hazards
SECTION 11: Toxicological information: Inhalation
GHS: Classification

Training information

Follow training instructions when handling this material.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.