



ZEROTRI® HEAVY-DUTY DEGREASER



FEATURES

- Fast acting solvent for degreasing parts and equipment
- Penetrating action instantly removes oil, grease, wax, dirt, moisture, and other contaminants
- Heavy-duty penetrating degreaser
- No ozone depleting chemicals
- No rinsing, no residue
- Does not contain chlorinated solvents
- NSF® registered C1 #059845 aerosol #059846 bulk
- Acceptable for use in Canadian Food Processing Establishments

MANUFACTURING APPLICATIONS

- Air Compressors
- Bearings
- Chains
- Cranes
- Forklifts
- Gears
- Ink Removal from Printing Presses
- Pulleys

SPECIFICATIONS AND APPROVALS

- Halliburton
- Kimberly-Clark
- Timken Steel
- PlastiPack Packaging
- Kodak
- Caterpillar
- NSF International
- Canadian Food Inspection Agency
- Honda Corp.
- Pratt & Whitney Canada MMC 21530
- Boeing BAC 5750 Rev. J

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
03520	C03520	15 wt. oz./425 g/563 mL	Aerosol	12	15.0 lbs.
03528	C03528	1 gal. (3.78 L)	Can	4	30.0 lbs.
03505	C03505	5 gal. (18.93 L)	Pail	1	36.0 lbs.
03555	C03555	55 gal. (208 L)	Drum	1	346.0 lbs.

PROPERTIES

Appearance/physical state	Gas / Aerosol; Liquid / Bulk
Odor	Ether-like/Fruity
Melting point/freezing point	Not established
Boiling point/range	> 132.8°F (> 56°C)
Vapor pressure	> 75 mm Hg @ 20°C
Partition coefficient	Not established
Percent volatile	100%
Flammability limit	Flammability limit - lower (%) 1.2% Flammability limit - upper (%) 12.8%
Propellant	Carbon dioxide (Aerosol)
VOC Content	Aerosol - 62.4%; Bulk - 65% U.S. State and Federal Consumer Product Regulations
Color	Clear/Colorless
Flash point	1.4°F (-17.0 °C) Tag Closed Cup
Relative density	Not established
Evaporation rate	> 1 (BuAc = 1)
Vapor density	~ 3 (air = 1)
Auto-ignition temperature	Not established
Viscosity	Not established
Specific Gravity (water=1)	0.74 - 0.76 @ 20°C
Solubility (water)	35% w/w
Temperature Range °F(°C)	Not available
4-Ball Weld Load	Not applicable

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Keep away from heat and sources of ignition. (See Section 7 of the SDS)

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2018 ITW Pro Brands • LPS® and ZeroTri® are registered trademarks of Illinois Tool Works All Rights Reserved • TDS03520 • 180605