



# ThermaPlex® FoodLube

## Bearing Grease



### FEATURES

- NSF® Registered H1 #117848
- Acceptable for use in Canadian Food Processing Establishments
- Uses only FDA listed ingredients
- Ensures safety in areas where incidental food contact may occur
- High degree of water washout resistance
- Excellent corrosion protection
- Very good load capacity
- Does not contain solvents or silicone
- Non-staining and non-emulsifying
- Metal Detectable Plastic Cap

### APPLICATIONS

- Blending Machines
- Carton Erectors
- Feed Belts
- Filling Equipment
- Frequent Wash Down Area
- Labeling Stations
- Wrapping Equipment

### SPECIFICATIONS AND APPROVALS

- Meets FDA Regulation 21 CFR 178.3570

#### IS (IDENTIFICATION SYSTEM)



### AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
70114	C70114	14.1 oz. (400 g)	Cartridges	30	32 lbs.
70155	C70155	55 gal. (400 lbs.)	Drum	1	450 lbs.

### PROPERTIES

Appearance/Physical State	Solid/Paste
Odor	Hydrocarbon-Like
Melting Point/Freezing Point	Not Available
Boiling Point/Range	Not Available
Vapor Pressure	< 0.13 kPa
Base Oil Type	USP Grade White Mineral Oil
Base Oil Viscosity	580 SUS @ 100°F 112 cst. @ 40°C 11 cst. @ 100°C
Copper Corrosion	1a/1b
Dropping Point °F(°C)	500°F (260°C)
NLGI Grade	2
Thickener Type	Aluminum Complex
Water Washout	3.50%
Color	White
Flash Point	400.0°F (204.4°C) Cleveland Open Cup
Relative Density	0.87, 7.506 (lbs/gal) @ 15°C
Evaporation Rate	Not available
Vapor Density	< 1 (air = 1)
Auto-ignition Temperature	Not Available
Viscosity	Not Available
Specific Gravity (water=1)	0.96
Temperature Range °F(°C)	-4°F (-20°C) to 300°F(149°C)
4-Ball Weld Load	>315 kg

### DIRECTIONS

For use in areas where incidental food contact may occur or in applications where clean, non-toxic lubricants are preferred. Apply either manually or by a suitable applicator. For best results, bearings should be purged of their previous lubricant before introducing new grease.

### HANDLING

Observe good industrial hygiene practices.

### STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.lpslabs.com](http://www.lpslabs.com)

©2018 ITW Pro Brands • LPS® and Thermaplex® are registered trademarks of Illinois Tool Works All Rights Reserved • TDS70114 • 181012