



LPS 3[®] PREMIER RUST INHIBITOR



FEATURES

- Protects for up to 2 years indoors
- Prevents rust and corrosion
- Self-healing, soft, waxy film
- Penetrates to displace moisture
- Inhibits exfoliation and filiform corrosion of aluminum
- Safe on all metals
- NSF[®] Certified: H2 Registration #129027 (Aerosol); #059849 (Bulk)
- Acceptable for use in Canadian Food Processing Establishments



APPLICATIONS

- Aircraft fuselages
- Battery terminals
- Cables, chains, and pulleys
- Cargo sections
- Interior sections of vehicle doors
- Metal parts
- Pumps and hose assemblies

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
00316	C30316	11 wt. oz. (312 mL)	Aerosol	12	12 lbs.
00322	C00322	20 fl. oz. (591 mL)	Trigger	12	18 lbs.
03128	C03128	1 gal. (3.78 L)	Container	4	33 lbs.
00305	C00305	5 gal. (18.93 L)	Pail	1	39 lbs.
00355	C00355	55 gal. (208 L)	Drum	1	408 lbs.



LPS 3[®] PREMIER RUST INHIBITOR

PROPERTIES

Appearance / Physical State	Liquid	Color	Brown
Odor	Mild. Cherry.	Flash Point	Aerosol: 64.4°F (18.0°C)TCC Bulk: 104.5 °F (40.3°C)TCC
Evaporation Rate	151 (Ethyl Ether)	Percent Volatile	63% - 82%
Density	7.28 lb/gal	Specific Gravity	0.87
Auto-ignition Temperature	446°F (230°C)	Flammability Limits	Lower 0.6% Upper 6%
Wet Film Thickness	3 - 7 mils	Pour Point °F (°C)	0°F (-18°C)
Humidity Cabinet Test (ASTM D 1748)	No rust on 1029 steel panels after 30 days	Coverage per gallon	401 ft ² /gallon @ 4 wet mils
Dry Film Thickness	1 - 3 mils	Salt Spray Cabinet Test (ASTM D 117)	No corrosion on 2024-T3 aluminum panels after 1500 hours
Corrosion Protection	Indoors: up to 2 years Outdoors: 9 months	VOC	Aerosol: 62.8 % per U.S. State and Federal Consumer Product Regulations Bulk: 75.58 % per U.S. State and Federal Consumer Product Regulations

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°F/122°F. Do not puncture, incinerate or crush. Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2017 ITW Pro Brands • LPS[®] and LPS 3[®] are registered trademarks of Illinois Tool Works All Rights Reserved • TDS00316 • 170505