



FEATURES

- May be used in wet or outdoor conditions
- NSF Certified: H1 Registration #134508
- Prevents belt slippage on flat, round, and V-belts; eliminates squeaks
- Contains no chlorinated solvents that deteriorate drive belts
- Water Resistant
- Metal Detectable plastic components

APPLICATIONS

- Appliance Drive Belts
- Bearings
- Bushings
- Flat Belts
- Polishing Belts
- Round Belts

SPECIFICATIONS AND APPROVALS

- General Motors Co.
- Ford Motor Co.
- Canadian Food Inspection Agency
- NSF International
- Whirlpool
- Kimberly-Clark

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
02216	C02216	10 wt. oz./284 g/445 mL	aerosol	12	11 lbs.

PROPERTIES

Appearance/physical state	Gas
Odor	Hydrocarbon-like
Melting point/freezing point	N/A
Boiling point/range	195.8°F (91°C) (concentrate)
Vapor pressure	352 mmHg @ 100°F (38°C)
Partition coefficient	N/A
Percent volatile	90%
Flammability limit	lower: 0.6%; upper: 7%
Propellant	Propane/Butane
VOC Content	90%
Color	Colorless
Flash point	19.4°F (-7.0°C) (TCC)
Relative density	N/A
Evaporation rate	> 1 BuAc (<1; ethyl ether = 1)
Vapor density	N/A
Auto-ignition temperature	788°F (420°C)
Viscosity	N/A
Specific Gravity (water=1)	0.67 - 0.69 @ 20°C
Temperature Range °F(°C)	32°F (0°C) to 325°F (163°C)
Coverage	34 ft2/can @ 5 wet mils; 17 ft2/can @ 10 wet mils

DIRECTIONS

Shake well before using. Turn off equipment and stop belts before applying. Spray inner surface of belt from a distance of 6 to 8 inches. Use only enough to cover belt. Let vapors dissipate. If desired, attach extension tube for difficult to reach areas. Repeat as needed. Avoid contamination of food in the application and storage of the product. Do not add directly to food. Use only in well ventilated areas. Avoid all sources of ignition (spark or flame).

HANDLING

Turn can upside-down and spray to clear nozzle. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling.

STORAGE

Keep container closed and in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F. Store aerosols as Level 3 Aerosol (NFPA 30B). Product is stable under recommended storage conditions. Keep away from heat and ignition sources. Do not expose to direct sunlight for extended periods.

DISPOSAL INFORMATION

Waste must be disposed of in accordance with national, regional, provincial, and local environmental control regulations.