



CFC Free Electro Contact Cleaner



FEATURES

- Excellent multi-purpose lubricant
- Ideal for electrical/electronic and fine parts
- Cleans and degreases delicate precision mechanisms
- Penetrating action removes oil, grease, dirt, flux and other contaminants
- NSF® Certified: K2 Registration # 059813 (Aero-sol); # 059814 (Bulk)



APPLICATIONS

- Cables
- Circuit Breakers
- Connectors
- Contacts
- Electric Motors
- Fluid Systems
- Generators
- Hinges
- Ignition Systems
- Locks
- Micrometers
- Office Equipment
- Power Tools
- Precisions Open Gears
- Relays and Controls
- Semiconductor assemblies
- Switch Gears
- Switched

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.	Net Contents	Container	Case Pack	Case Wt.
03116	11 wt. oz. (312 g)	Aerosol	12	12 lbs.
03101	1 gal. (3.78 L)	Container	4	35 lbs.
03105	5 gal. (18.93 L)	Pail	1	38 lbs.
03155	55 gal. (208 L)	Drum	1	385 lbs.



CFC Free Electro Contact Cleaner

PROPERTIES

Appearance/physical state	Liquid	Color	Clear water-white
Odor	Solvent	Flash point	<1.4°F (<-17.0°C) TCC
Solubility (water)	<10% w/w	Auto-ignition temperature	582.8°F (306°C)
Initial boiling point	140.9°F(60.5°C)	Evaporation rate	<1 (Ethyl Ether = 1)
Vapor pressure	352.53 mm Hg @ 38°C	Vapor density	~3 (air = 1)
Viscosity	<3 cSt @ 25°C	Partition coefficient	>1
Flammability limit	lower 0.6% upper 7%	VOC	96.2% per US State and Federal Consumer Product Regulations

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

DIRECTIONS

Shake well before using. Hold can upright and spray from 10-12 inches away. Use attached extension tube for pinpoint application. Apply a light coating. Reapply as needed.

DO NOT USE ON ENERGIZED ELECTRICAL EQUIPMENT OR EQUIPMENT IN OPERATION AND ALLOW SURFACE TO DRY BEFORE RESTART.

DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.



800.241.8334 | www.lpslabs.com

TDS02016 160701

STORAGE

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Protect from freezing.